



BURNDY Catalog Number	K2A29U
UPC Number	781810600108
Description	TWO:6STR-250 DUAL RATED
Status	Active

Web Use  
BURNDY Product Line

Dimensional	
Width (in)	1.66
Length (in)	2.56
Bolt Hole Size (in)	0.38
Thickness	0.25
D - in	1.5
Pad Width (in)	1.66
N (in)	0.5
General	
Number of Conductors	2
Number of Holes	1
Product Description	Aluminum Universal Terminal, 2 Conductor, 1 Hole, 6 AWG (Str)-250 kcmil, 3/8" Stud, 2 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	6 AWG-250 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	6 AWG-250 kcmil
Physical	
Installation Torque	275
Type of Plating	Unplated
Connector Type	Terminal
Bolt Hole Size	3/8
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA  
47, industrial Park Drive  
Manchester NH03109

BURNDY Technical Services  
47, industrial Park Drive  
Manchester NH03109

Hours: 8.00 AM - 5.00 PM  
Monday - Friday  
Phone: 000-346-4175

