



Main

Range of product	Acti 9
Modular device name	IHP
Device short name	IHP 1c 18 mm
Product or component type	Programmable digital time switch
Number of channels	1
Battery type	Lithium
Function available	Automatic time changeover Operating hours counter
Type of setting	Absence for holidays function PIN code
Provided equipment	Memory key Programming kit
Language	Dutch English French Italian Portuguese Spanish

Complementary

Device application	Building
Measurement accuracy	+/- 0.5 s/day
Cycle duration	24 hours + 7 days
Maximum number of switchings	56
Minimum interval duration	1 min
Measurement accuracy	+/- 0.5 s/day 25 °C
Power consumption	0.4 W
Maximum switching current	4 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
[Ue] rated operational voltage	230 V (+10 % -15 %) AC 50/60 Hz
Display type	LCD
Battery life	10 yr
Backup time	10 years time and program saving
Product mounting	DIN rail
9 mm pitches	2
Colour tint	White(RAL 9003)
Connections - terminals	Screwless terminals : 2 x 0.5...2.5 mm ²
Width	18 mm
Height	90 mm
Depth	66 mm
Product weight	90 g

Environment

Ambient air temperature for operation	-25...55 °C
IP degree of protection	IP20 B

Contractual warranty

Period	18 months
--------	-----------