



Main

Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	12
Nb of horizontal rows	3
Type of door	Translucid
Width	294 mm outside 270 mm wall
Height	502 mm outside 478 mm wall
Depth	80 mm wall 18 mm outside

Complementary

Enclosure mounting	Flush
Total number of 18 mm modules	36
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Earth
Number of terminal blocks	1 earth terminal block with 20 screwed outgoers
Distribution block outgoers	9 x 6 mm ² for earth 9 x 10 mm ² for earth 2 x 16 mm ² for earth
Enclosure material	Front face: technoplastic Door: technoplastic Back part: technoplastic
Colour	Door: translucid Front face: white (RAL 9003)

Environment

Standards	EN 50102 IEC 529 IEC 60439-3 IEC 60670-24 IEC 60695-2-11
Quality labels	IMQ
Fire resistance	Front face: 750 °C Door: 650 °C Back part: 850 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------