



Main

Range of product	Compact CVS100...250 NSX100...250
Poles description	3P
Earth-leakage add-on module name	ME
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Fixed
[I Δ n] residual earth-leakage sensitive adjustment	0.3 A
Residual earth-leakage time delay adjustment type	Fixed
[Δ t] residual earth-leakage time delay adjustment	< 40 ms

Complementary

Network type	AC
Network frequency	50/60 Hz
[I _n] rated current	100 A 160 A
[U _e] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	< 40 ms

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2
RoHS EUR conformity date	0818
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.