

A9N61521

miniature circuit breaker - C60H - 2 poles - 1 A - C
curve



Main

| | |
|-----------------------------|--|
| Circuit breaker application | Distribution |
| Range of product | C60 |
| Product or component type | Circuit breaker |
| Device short name | C60H-DC |
| Poles description | 2P |
| Number of protected poles | 1 |
| [In] rated current | 1 A at 25 °C |
| Network type | DC |
| Trip unit technology | Thermal-magnetic |
| Curve code | C |
| Breaking capacity | 10 kA Icu conforming to EN 60947-2 - 440 V DC 10 kA Icu conforming to IEC 60947-2 - 440 V DC 6 kA Icu conforming to EN 60947-2 - 500 V DC 6 kA Icu conforming to IEC 60947-2 - 500 V DC 20 kA Icu conforming to GB 14048.2 - 220 V DC 20 kA Icu conforming to IEC 60947-2 - 220 V DC 20 kA Icu conforming to GB 14048.2 - 250 V DC 20 kA Icu conforming to IEC 60947-2 - 250 V DC |
| Utilisation category | Category A conforming to EN 60947-2 Category A conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to EN 60947-2 Yes conforming to IEC 60947-2 |

Complementary

| | |
|--|--|
| Network frequency | - |
| [Ue] rated operational voltage | 500 V DC |
| Magnetic tripping limit | 7...10 x In |
| [Ics] rated service breaking capacity | 15 kA 75 % x Icu conforming to EN 60947-2 - 220 V DC 15 kA 75 % x Icu conforming to IEC 60947-2 - 220 V DC 15 kA 75 % x Icu conforming to EN 60947-2 - 250 V DC 15 kA 75 % x Icu conforming to IEC 60947-2 - 250 V DC 4.5 kA 75 % x Icu conforming to EN 60947-2 - 500 V DC 4.5 kA 75 % x Icu conforming to IEC 60947-2 - 500 V DC 7.5 kA 75 % x Icu conforming to EN 60947-2 - 440 V DC 7.5 kA 75 % x Icu conforming to IEC 60947-2 - 440 V DC |
| [Ui] rated insulation voltage | 500 V DC conforming to IEC 60947-2 500 V DC conforming to EN 60947-2 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN 60947-2 6 kV conforming to IEC 60947-2 |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | ON/OFF indication |
| Mounting mode | Fixed |
| Mounting support | 35 mm symmetrical DIN rail |
| Comb busbar distribution block compatibility | Standard top or bottom |
| 9 mm pitches | 4 |
| Height | 81 mm |
| Width | 36 mm |
| Depth | 73 mm |
| Product weight | 0.256 kg |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 6000 cycles - 500 V DC |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

3000 cycles - 500 V DC

| | |
|-----------------------------|---|
| Provision for padlocking | Padlockable |
| Locking options description | In position O |
| Connections - terminals | Tunnel type terminals, top or bottom for 1 flexible wire(s) 16 mm ² max Tunnel type terminals, top or bottom for 1 rigid wire(s) 25 mm ² max |
| Tightening torque | 2.5 N.m top or bottom power circuit |
| Earth-leakage protection | Without |
| Product compatibility | C60 accessories C60 auxiliary |

Environment

| | |
|---------------------------------------|---|
| Standards | EN 60947-2 IEC 60947-2 |
| Pollution degree | 3 conforming to EN 60947-2 3 conforming to IEC 60947-2 |
| Tropicalisation | 2 conforming to IEC 60068-2 |
| Relative humidity | 95 % 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 1310 - Schneider Electric declaration of conformity |