

# 16A23-B

## Single Pole Devices



Color:  Blue

UPC Code: 07847799072

Country of Origin: Please Contact Customer Service

### SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**  
201 North Service Road, Melville, NY 11747  
Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**  
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 · FAX: 1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**  
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)  
© 2012-2015 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

**Leviton has a global presence.**  
If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

### Brand Features

The 16 Series Taper Nose products are the connectors of choice for concerts, sound stages, movie-making, television production, sporting events and conventions.

### Item Description

16 Series Commercial Grade Multi-Way Connector, Cam-Type, Taper Nose, Male-Female-Female-Female, 3-Fer, 400 Amp - BLUE

### Technical Information

#### Electrical Specifications

**Max. Amperage:** 400 Amp

**Max. Voltage:** 600 Volt

#### Material Specifications

**Sleeve Material:** Santroprene TPV

**Contact Material:** Brass

**Strain Relief:** Copper Wire

#### Mechanical Specifications

**Gender:** Male-Female-Female-Female

#### Product Features

**Color:** Blue

#### Standards and Certifications

**UL Listed:** File E-13399

**CSA Certified:** File 152105

**NEMA Rating:** Type 3R

