

# Uniones Manguito Cerrado

Conector tubular para empalme de cobre electrolítico con una capa de estaño de 7 micras. Con una capacidad de tensión de 35 KV.

| Calibre (mm <sup>2</sup> ) | Cable   | Largo <sup>(1)</sup> (mm) | Largo <sup>(2)</sup> (mm) | Espesor (mm) |
|----------------------------|---------|---------------------------|---------------------------|--------------|
| 10                         | 8 AWG   | 30.0                      | 32.0                      | 1.2          |
| 16                         | 6 AWG   | 35.0                      | 50.0                      | 1.3          |
| 25                         | 4 AWG   | 40.0                      | 50.0                      | 1.3          |
| 35                         | 2 AWG   | 45.0                      | 50.0                      | 1.7          |
| 50                         | 1/0 AWG | 50.0                      | 55.0                      | 1.7          |
| 70                         | 2/0 AWG | 55.0                      | 55.0                      | 1.7          |
| 95                         | 4/0 AWG | 60.0                      | 70.0                      | 2.3          |
| 120                        | 250 MCM | 65.0                      | 70.0                      | 2.5          |
| 150                        | 300 MCM | 70.0                      | 80.0                      | 2.5          |
| 185                        | 400 MCM | 75.0                      | 85.0                      | 2.9          |
| 240                        | 500 MCM | 80.0                      | 90.0                      | 2.9          |
| 300                        | 600 MCM | 85.0                      | 100.0                     | 3.0          |

(1) medidas estandar

(2) medidas normalizadas

